



**Rymar LLC**  
6620 N CTH J  
Cato, WI 54230

Phone: 1-866-287-9627  
Customer Service: rymar@rymarindustries.com

**25025**

**SAFETY DATA SHEET**

**PAGE: 1**

**1.0 PRODUCT AND SUPPLIER IDENTIFICATION**

|                            |                             |                        |
|----------------------------|-----------------------------|------------------------|
| <b>PRODUCT CLASS</b>       | <b>TRADE NAME</b>           | <b>MFG PRODUCT NO.</b> |
| INDUSTRIAL COATING PRODUCT | #25025 NATURAL CEDAR SEALER | 47-754J                |

**Identified Uses:** CONSUMER PRODUCT, RESINS AND PAINT RELATED MATERIALS

**Supplier:** RYMAR LLC.  
6620 North CTH J  
CATO, WI 54230

**Emergency Contact:** Transportation Emergency (24 hour) 1-800-924-6804

**Other Contacts** Customer Service (866) 287-9627  
**rymar@rymarindustries.com**  
  
**www.rymarindustries.com**

**2.0 HAZARDS IDENTIFICATION**

| <b>Classification</b>                              | <b>Cat</b> | <b>HCODE</b> | <b>Description</b>  |
|--|------------|--------------|---|
| Flammable liquid                                   | 3          | H226         | Flammable liquid and vapor  |
| Aspiration hazard                                  | 1          | H304         | May be fatal if swallowed and enters airways                      |
| Specific target organ acute irritation-respiratory | 3          | H335         | May cause respiratory irritation                                  |
| Specific target organ acute narcotic effects (CNS) | 3          | H336         | May cause drowsiness or dizziness                                 |
| Eye irritant 2A                                    | 2          | H319         | Causes serious eye irritation                                     |
| Skin irritation                                    | 2          | H315         | Causes skin irritation  |
| Cell mutagenicity 1B                               | 1          | H340         | May cause genetic defects   |
| Specific target organ chronic toxicity (CNS)       | 2          | H373         | May cause damage to organs through prolonged or repeated exposure |
| Acute toxicity inhaled gases/vapors/dust/mist      | 4          | H332         | Harmful if inhaled  |
| Acute toxicity dermal                              | 4          | H312         | Harmful in contact with skin                                      |
| Suspect carcinogen                                 | 2          | H351         | Suspected of causing cancer                                       |
| Chronic aquatic toxicity                           | 3          | H412         | Harmful to aquatic life with long lasting effects                 |
| Suspected of damaging the unborn child             | 1          | H360         | May damage fertility or the unborn child                          |
| Acute toxicity oral                                | 4          | H302         | Harmful if swallowed  |
| Skin sensitizer 1B                                 | 1          | H317         | May cause an allergic skin reaction                               |

**Precautionary Statements:**

Keep away from heat/sparks/open flames/hot surfaces. NO SMOKING.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical, ventilation, and lighting.

Use only non-sparking tools.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

DO NOT induce vomiting.

Store locked up, KEEP AWAY FROM CHILDREN.

Dispose of contents/container to licensed waste facility in accordance with local and national regulations, see SDS section 13 for additional information.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor/physician if you feel unwell.

Store in a well ventilated place. Keep container tightly closed.

Wash face, hands, and any exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/ face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing eyes.  
If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with soap and water.

See specific treatment for first aid in SDS section 4.

If skin irritation occurs: Get medical advice/attention.

Obtain special instructions before use, read SDS and product specification sheet.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as specified in section 8.

IF exposed or concerned: Get medical advice/attention.

Do not breathe dust/fume/gas/mist/vapors/spray.

Get medical advice/attention if you feel unwell.

See specific measures for safe handling in SDS sections 7 and 13.

Wash contaminated clothing before reuse.

Avoid release to the environment.

Do not eat, drink or smoke when using this product.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.  
Rinse mouth.

Contaminated work clothing should not be allowed out of the workplace.

If skin irritation or a rash occurs: Get medical advice/attention.

Signal Word: DANGER



**Other hazards which do not result in classification:**

Use in a well ventilated area.

Do not take internally. Do not get in eyes or on skin.

May cause eye and skin irritation.

May cause irritation of the respiratory tract.

Maintain a clean work area, remove rags and wastes daily. Store waste and used rags in approved containers.

Do not eat, drink or smoke when using this product. Wash face, hands and any exposed skin thoroughly after handling.

Take precautionary measures against static discharge.

May cause allergic reaction in special sensitive persons.

This product contains a pesticide that is toxic to fish.



3.0 COMPOSITION AND INFORMATION ON INGREDIENTS

| INGREDIENT                     | CAS#           | ACGIH TLV |       | ACGIH STEL |       | OSHA PEL |       | OSHA CEILING |       | LEL %<br>VOLUM | VAPOR PRESS |       | % BY<br>Wght |
|--------------------------------|----------------|-----------|-------|------------|-------|----------|-------|--------------|-------|----------------|-------------|-------|--------------|
|                                |                | PPM       | mg/m3 | PPM        | mg/m3 | PPM      | mg/m3 | PPM          | mg/m3 |                | mm/Hg       | DEG F |              |
| Aromatic Petroleum Distillate  | 64742-95-6     | -----     | ----- | -----      | ----- | 100.0    | ----- | -----        | ----- | 1.000          | 3.000 @ 68. |       |              |
| C Xylene (mixed isomers)       | VHAP 1330-20-7 | 100.0     | 434.0 | 150.0      | 651.0 | 100.0    | 435.0 | -----        | ----- | 1.000          | 5.100 @ 68. | 1.17  |              |
| A 1,2,4-Trimethylbenzene       | 95-63-6        | 25.00     | 123.0 | -----      | ----- | 25.00    | 125.0 | -----        | ----- | 0.900          | 1.000 @ 56. | 10.2  |              |
| C Ethyl Benzene                | VHAP 100-41-4  | 20.00     | 87.00 | 125.0      | 543.0 | 100.0    | 435.0 | -----        | ----- | 1.000          | 10.00 @ 79. | 0.29  |              |
| Raw Linseed Oil                | 8001-26-1      | -----     | ----- | -----      | ----- | -----    | ----- | -----        | ----- | -----          | -----       | @ --- |              |
| Hydrotreated Distillates Light | 64742-47-8     | 100.0     | ----- | -----      | ----- | 300.0    | ----- | -----        | ----- | 0.700          | 1.000 @ 68. |       |              |

C -This toxic chemical is subject to the reporting requirements of both Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372) and the Wisconsin Dept. of Natural Resources Administrative Code Chapter NR445.

VHAP = VOLATILE HAZARDOUS AIR POLLUTANT (VAPOR)

HAP = HAZARDOUS AIR POLLUTANT (SOLID)

(skin) = OSHA Skin Absorption Hazard

VOC content determined by EPA method 24.

A -This toxic chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).

VHAP = VOLATILE HAZARDOUS AIR POLLUTANT (VAPOR)

HAP = HAZARDOUS AIR POLLUTANT (SOLID)

VOC content determined by EPA method 24.

|                                  | BY WEIGHT      | BY VOLUME        |
|----------------------------------|----------------|------------------|
| PERCENT SOLIDS                   | : 40.73        | 36.60            |
| PERCENT WATER                    | : .22          | .20              |
| PERCENT NON-EXEMPT SOLVENT       | : 59.05        | 63.20            |
| PERCENT EXEMPT SOLVENT           | :              |                  |
| VOC (WITH WATER AND EXEMPT SOLV) | : 4.47 LBS/GAL | 535.68 GMS/LITER |
| VOC (LESS WATER AND EXEMPT SOLV) | : 4.48 LBS/GAL | 536.88 GMS/LITER |
| PERCENT HAPS BY WEIGHT           | : 1.90         |                  |
| VOC LBS PER GALLON SOLIDS        | : 12.21        |                  |
| VOC KILOGRMS PER KILOGRMS SOLIDS | : 1.45         |                  |
| VOC HAPS LBS PER GALLON SOLIDS   | : .39          |                  |
| VOC HAPS LBS PER LBS SOLIDS      | : .05          |                  |

4.0 FIRST AID MEASURES

GENERAL ADVICE: If you feel unwell seek advice immediately. Physicians: treat exposures symptomatically & supportively.

FIRST AID FOR EYE CONTACT: Flush the eyes and eyelids with plenty of water for at least 15 minutes. Hold eyelids apart to ensure flushing of the entire area. Remove contact lenses if present and easy to do. Get medical attention.

FIRST AID FOR SKIN CONTACT: Remove contaminated clothing & contaminated shoes. Wash all affected areas with soap & water for 10 minutes. Get medical attention if you feel ill.

FIRST AID FOR INHALATION: Move exposed individual to fresh air. For any difficulty in breathing, give oxygen and get immediate emergency medical assist. Monitor for respiratory distress. Be prepared to give rescue breathing. If unconscious, place in recovery position with airway open. Loosen tight clothing.



FIRST AID FOR INGESTION: Get IMMEDIATE medical attention. Rinse mouth with water. Remove dentures if any. Remove to fresh air and keep at rest in a comfortable breathing position. Aspiration hazard if swallowed. Can enter lungs. DO NOT INDUCE VOMITING. Keep head low so that any fluids do not enter the lungs. Never give anything by mouth to an unconscious or convulsive person. If unconscious, place in recovery position with airway open. Loosen tight clothing. IF A LARGE QUANTITY IS INGESTED, CALL A POISON CENTER OR CONTACT A LOCAL EMERGENCY MEDICAL SERVICE AT ONCE. MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: None known, no specific information available.

=====

## 5.0 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, CO2, alcohol resistant foam. Use water spray or fog for cooling containers. Use water with caution. Water may be ineffective.

UNUSUAL FIRE & EXPLOSION HAZARDS: Keep containers tightly closed, isolate from heat, open electrical equipment, sparks and open flames. Used containers may explode when exposed to high heat. DANGER! Rags, steel wool, or waste soaked with product may spontaneously catch fire if improperly discarded or stored. Immediately after use, place rags or waste in a sealed water-filled metal container.

SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure buildup. Use water spray to cool fire exposed containers if they cannot be safely moved. Keep people away from firefighting operations involving chemicals. Firefighters wear a self-contained positive pressure breathing apparatus in addition to full protective gear.

CAUTION! Manage firefighting runoff water. Prevent possible toxic runoff from entering watersheds or storm sewers. WARNING! Sudden release of hot organic chemical vapors from equipment operating at elevated temperatures or sudden introduction to vacuum conditions may result in ignition.

=====

## 6.0 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Provide adequate ventilation to spill area. Dike spill area and collect with inert absorbent, sand, earth. Avoid contact and vapors, see approved PPE devices listed in Section 8. Follow all local, state and federal spill reporting rules. Only properly trained personnel should clean spill hazards. Personnel without proper PPE should leave the spill area. Obtain professional emergency/clean up services as needed.

ENVIRONMENTAL CONCERN: This product may contain a reportable quantity of a hazardous substance. Follow all local, state, provincial and/or federal reporting procedures. Do not allow product to enter drains, sewers or waterways. Consult a professional cleaning or waste disposal service. Treat both spill residue and empty container residue as hazardous.

WASTE DISPOSAL CONSIDERATIONS: Waste must be disposed in accordance with local, state, provincial and/or federal regulations. Empty containers must be handled with care as they retain product residue. Before disposing containers, remove as much residue as possible. Do not reuse containers until they are properly recycled. Check Section 13 for waste disposal options. Follow all label and SDS warnings.

=====

## 7.0 HANDLING AND STORAGE

ADVICE ON SAFE HANDLING: Wash hands thoroughly after handling. Wear proper PPE, eye protection, gloves and respirator. Maintain good housekeeping. Eye wash stations should be available in the workplace. Avoid puncturing the container, do not drag or drop. Spray operations must protect the worker from both vapors & spray/mist overspray. Keep from Freezing.

CONDITIONS FOR SAFE STORAGE: Keep all containers tightly closed. Keep away from excessive heat and sunlight. Storage temperatures should be between 40-100 degrees F.

NOTE: Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring materials. Use explosion proof electrical and ventilation and material handling equipment.

NOTE: Limit application processes to the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.



=====

## 8.0 EXPOSURE CONTROL / PERSONAL PROTECTION

**SELECTING PROTECTIVE EQUIPMENT AND CLOTHING:** When choosing personal protective equipment and clothing, consider each worker's environment, ventilation, temperature, all chemical exposures and any other adverse physical conditions. The level of protection needed for eye/skin, respiratory and other protection should be part of an ongoing job safety analysis conducted by the end user and supervisor. Safety Data Sheet Sections 2,3,8 and 11 should be consulted.

**EXPOSURE CONTROLS:** Provide sufficient mechanical or natural ventilation or exhaust to maintain exposures below limit guidelines or below levels that cause known, suspect or apparent side effects or the formation of dust or vapors. Allow easy access to emergency shower/eye wash facilities. Wash any contaminated clothing before reuse.

**SKIN PROTECTION:** Chemical resistant gloves are recommended. Use neoprene, Viton or butyl rubber. If nitrile gloves are used they should be approved for exposure to the chemicals listed in section 2. The use of barrier creams should be minimized. Chemical resistant footwear and outer garment are recommended to prevent skin absorption. Consult your safety supply vendor for optimum personal protection equipment.

**EYE PROTECTION:** Eye protection should be worn in any type of industrial operation. The use of safety glasses with side shields (or goggles) and a face shield is recommended to prevent against liquid splash. Contact lenses should not be worn.

**VENTILATION:** Provide sufficient ventilation to keep hazards at levels below current ACGIH TLV and OSHA PEL exposure levels for the hazardous ingredients listed in Section 3. Use explosion-proof ventilation equipment. Provide proper respiratory protection if ventilation or exhaust is inadequate.

**RESPIRATORY PROTECTION:** In outdoor or open areas with good ventilation additional precautions should not be needed. If exposure limits are exceeded or if irritation is experienced, use a NIOSH approved respirator. Use a SCBA for confined spaces or poor ventilation. Follow the OSHA prescribed respiratory protection program guidelines for the chemicals found in Section 3. Consult your safety supplier for the correct respirator system specifications.

**OTHER PROTECTIVE EQUIPMENT:** The use of chemical resistant protective suit is suggested. Avoid any skin contact with vapors, mists, or spray. Prevent contact of materials with clothing if possible. Remove and wash contaminated clothing before re-use. Use an industrial type professional cleaning service, do not wash at home. Do not wear contaminated clothing or shoes away from the workplace. Leather products contaminated with this product should be discarded.

Exposure Limits For Inert and Nuisance Dust Particulates Not Otherwise Classified: OSHA (PEL): TWA =15 mg/m3 (total dust) 5 mg/m3 (respirable fraction). ACGIH(TLV): TWA = 10 mg/m3 (total dust).

Exposure Limits For iron oxide (fume): (CAS# 1309-37-1) OSHA (PEL): TWA =10 mg/m3 (as total particulates) ACGIH(TLV): TWA = 5 mg/m3.

=====

## 9.0 PHYSICAL AND CHEMICAL PROPERTIES



|                            |                         |
|----------------------------|-------------------------|
| APPEARANCE                 | BEIGE/AQUA LIQUID       |
| ODOR                       | Chemical                |
| ODOR THRESHOLD (ppm)       | 20                      |
| pH                         | N/A                     |
| FREEZING POINT             | N/A                     |
| BOILING RANGE              | 275-752 F               |
| FLASH POINT                | 105 F (ASTM D3828)      |
| EVAPORATION RATE           | SLOWER THAN WATER       |
| LEL% BY VOLUME             | SEE SECTION 3           |
| VAPOR PRESSURE             | SEE SECTION 3           |
| VAPOR DENSITY              | HEAVIER THAN AIR        |
| RELATIVE DENSITY (lbs/gal) | 7.5655                  |
| SOLUBILITY                 | SOLUBLE IN SOLVENT      |
| AUTOIGNITION TEMP          | >500 degrees Fahrenheit |
| DECOMPOSITION TEMP         | (Not determined)        |
| VISCOSITY                  | 15-18/2 ZAHN CUP        |

=====

## 10.0 STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable under normal storage conditions.  
HAZARDOUS POLYMERIZATION: Will not occur.  
CONDITIONS TO AVOID: Keep away from high heat, flame, spark, or static discharges. If exposed to extreme heat, sealed containers may explode. Container is not a pressure vessel. Do not use pressure to empty containers. Bonding/grounding procedures must be followed at all times, consult NFPA 30 "Flammable and Combustible Liquid Code".  
INCOMPATIBILITIES: Strong acids, strong alkalis, strong reducers, strong oxidizers.  
HAZARDOUS DECOMPOSITION PRODUCTS: May decompose to oxides of carbon, nitrogen, phosphorous, chlorine and/or sulphur. May also break down to release other irritating or toxic fumes if exposed to fire conditions.

=====

## 11.0 TOXICOLOGICAL INFORMATION

ROUTES OF ENTRY: Ingestion, inhalation, eye contact, skin contact absorption.  
ACUTE TOXICITY ORAL: LD50 (rat): >2,000 mg/kg  
ACUTE TOXICITY DERMAL: LD50 (rat): >2,000 mg/kg  
ACUTE TOXICITY INHALATION: LC50 (rat, 4h): >2,250 mg/m3  
SKIN CORROSION/IRRITATION: Causes moderate to severe skin irritation. May cause skin harm.  
SERIOUS EYE DAMAGE/IRRITATION: Causes eye irritation.  
RESPIRATORY SENSITIZATION: Non-sensitizing.  
SKIN SENSITIZATION: Lab animal sensitization. Some cases of sensitization also observed in humans.  
SINGLE DOSE TOXICITY: May have acute toxicity properites or specific target organ toxicity in acute exposures. See specific information in section 2 of this SDS.  
REPEATED DOSE TOXICITY: Chronic or repeated overexposure may result in damage to the tissues of the nose and upper respiratory system. See specific target organs listed in Section 2.  
ASPIRATION HAZARD: Aspiration may cause chemical pneumonitis and/or pulmonary edema as evidenced by coughing, labored breathing, cyanosis (bluish skin) or if severe aspiration may be fatal.  
REPRODUCTIVE TOXICITY: No positive results. No evidence of effects.  
GERM CELL MUTAGENICITY: Positive as well as negative results were found in mutagenicity testing.  
OTHER EFFECTS: Narcotic CNS effect. May cause drowsiness or dizziness. Intentional misuse by deliberately concentrating & inhaling vapors from this product may be harmful or fatal.



EFFECTS OF OVEREXPOSURE: There is no applicable information available regarding the carcinogen potential for this product as a whole, however any relevant information regarding any ingredient status as a potential, suspect, or confirmed carcinogen is listed in section 11 of the SDS.

CARCINOGEN POTENTIAL: This product contains benzene CAS# 71-41-2 which is classified as a confirmed human carcinogen, level A1 by ACGIH.

CARCINOGEN POTENTIAL: This product contains cumene CAS# 98-82-8 which is listed by IARC as a group 2B possible human carcinogen and by ACGIH as a confirmed animal carcinogen with unknown relevance to humans.

CARCINOGEN POTENTIAL: Ethylbenzene CAS# 100-41-4 is present in this product. Ethylbenzene has been classified by IARC as a possible human carcinogen group 2B.

CARCINOGEN POTENTIAL: Exposure to high concentrations of naphthalene may cause destruction of red blood cells, anemia and cataracts. Naphthalene is an IARC 2B animal carcinogen, the relevance to humans is uncertain. CAS# 91-20-3

Ingestion of alcohol can increase the effects of overexposure from some solvents in this product.

Prolonged and continuous exposure to excessive concentration of dust of any kind without using a dust mask may have an adverse pulmonary effect on some people. This overexposure may result in coughing, sputum, and reduced lung capacity.

Pre-existing asthmatic conditions may worsen. Persons with lung diseases should not work in dusty areas unless a physician certifies their fitness to wear a respirator. (OSHA 1910.134). Liquids do not pose a dust hazard.

This product contains iron oxide, which is currently listed by OSHA & ACGIH as a fume hazard. Overexposure to dried particles may pose hazards to the eyes, ears & nose. Injury to the skin or mucous membranes can occur by rigorous skin cleaning or direct mechanical abrasion. Long term exposure to dust without respiratory protection may cause siderosis, a benign pneumoconiosis. Liquid products would not pose a dust hazard.

=====

## 12.0 ECOLOGICAL INFORMATION

ECOTOXICITY FISH: LC50 (rainbow trout, 4d): 1-10 mg/l

ECOTOXICITY AQUATIC PLANTS: EC50 (algae, 3d): < 10 mg/l

ECOTOXICITY AQUATIC INVERTEBRATES: EC50 (daphnia magna, 48h) < 2 mg/l

ECOTOXICITY MICROORGANISMS: EC50 (bacteria, 2d): >8,000 mg/l

PERSISTENCE AND DEGRADABILITY: Partially soluble in water. This product is predicted to partially degrade in soil and water.

BIOACCUMULATION / ACCUMULATION: Very low potential.

MOBILITY IN SOIL: No data available or no known significant effects or critical hazards.

OTHER ADVERSE ECOLOGICAL EFFECTS: No data available.

=====

## 13.0 DISPOSAL INFORMATION

WASTE DISPOSAL PROCEDURE: This product contains a small quantity of a pesticide. Improper disposal of excess product or residue is a violation of federal law. Do not contaminate food, water, or feed by storage or disposal. This product is toxic to fish. Do not discharge into lakes, streams or other waters. Do not discharge to sewer systems without proper authorization. Follow all local, state, provincial and/or federal waste disposal codes.

CONTAMINATED PACKAGING: Empty remaining contents from containers. Empty containers should be disposed in a safe manner, do not allow residue to enter waterways. Do not heat or cut empty containers with electric or gas torch.

REGULATORY INFORMATION: This product contains a Marine Pollutant. Do not allow this product to be spilled into or near watersheds or bodies of water.

=====

## 14.0 TRANSPORTATION INFORMATION

PROPER SHIPPING NAME - NA1993, COMBUSTIBLE LIQUID, n.o.s.,III (PETROLEUM DISTILLATES) (NOT FOR AIR&INTERNATIONAL)

SHIPPING LABEL - NOT REGULATED IF QTY. LESS THAN 119 GALLONS



=====

## 15.0 REGULATORY INFORMATION

SARA 311/312 Hazards:

- Acute Health Hazard
- Chronic Health Hazard
- Fire Hazard

SARA 302 HAZARDS: No chemicals in this product are subject to the reporting requirements of SARA Title III Section 302.

SARA 304 HAZARDS: No chemicals in this product are subject to the reporting requirements of SARA Title III Section 304.

SARA 313 HAZARDS: This product contains chemical components that are reportable by SARA Title III section 313. They are listed in Section 3 of this Safety Data Sheet.

TSCA: All chemical substances in this product are listed by the Toxic Substance Control Act Inventory as required by 40CFR 700-799. This product complies with TSCA requirements.

CANADA 1988 WHMIS CLASSIFICATION:

B2: Flammable Liquid

D2A: Very Toxic Material Causing Other Toxic Effects possible carcinogen or embryo toxin or mutagen in animals

D2B: Toxic Material Causing Other Toxic Effects Eye and/or Skin irritation on animals

CALIFORNIA PROP 65: **WARNING:** This product contains products known to the State of California to cause cancer and/or birth defects or reproductive harm.

Benzene CAS# 71-43-2 Listed as causing cancer and developmental and male reproductive toxicity.

Cumene CAS# 98-82-8 Listed as causing cancer.

Ethyl benzene CAS# 100-41-1 Listed as causing cancer.

Naphthalene CAS# 91-20-3 Listed as causing cancer.

Toluene CAS# 108-88-3 Listed as causing developmental toxicity.

This product contains aromatic naphtha, light which is on the New Jersey and Pennsylvania Right-to-Know list.

CAS# 64742-95-6.

This product contains cumene which is on the Pennsylvania Massachusetts & New Jersey Right-to-Know lists. CAS# 98-82-8 (benzene, 1-methylethyl-)

This product contains ethyl benzene CAS#100-41-4 which is on the Pennsylvania, New Jersey and Massachusetts Right-to-Know Lists.

This product contains petroleum distillates CAS# 64742-47-8 which is on the New Jersey and Pennsylvania Right-to-Know Lists.

This product contains 1,2,4-trimethylbenzene which is on the Massachusetts, New Jersey & Pennsylvania Right-to-Know lists Specific CAS #95-63-6 or the mixed isomer CAS# 25551-13-7.

This product contains xylenes, mixed isomers which is on the New Jersey, Massachusetts & Pennsylvania Right-to-Know Lists (benzene, dimethyl-) CAS# 1330-20-7

SPECIAL HANDLING PRECAUTION: Avoid skin contact & ingestion. Keep away from food and watersheds. This product contains a registered pesticide that contains 3-Iodo-2-Propynyl Butyl Carbamate; CAS# 55406-53-6. EPA Reg. No. 464-8125-1448 or EPA Reg. No. 5383-112. This is a SARA 313 reportable chemical and is listed on the New Jersey Right-to-Know list.

=====

## 16.0 OTHER INFORMATION

NOTICE: The HMIS rating for this material involves data and interpretations compiled from the various material suppliers of the component ingredients. This information will vary from supplier to supplier. The rating is intended for rapid and general identification of this product's hazards. To adequately deal with the safe handling of this material, all information contained in the SDS must be reviewed as part of an ongoing Hazard Communication Program.





Rymar LLC  
 6620 N CTH J  
 Cato, WI 54230

Phone: 1-866-287-9627  
 Customer Service: rymar@rymarindustries.com

**25025**

**SAFETY DATA SHEET**

**PAGE : 9**

This safety data sheet was prepared to comply with the U.S. OSHA Hazard Communication Standard 29 CFR 1910.1200 and the international GHS recommendations. The most current dated copy supersedes any previous dated information. Older information should be deleted to avoid confusion. VOC data determined by US EPA method 24.

DEFINITIONS: HAP = Hazardous Air Pollutant VHAP = Volatile Hazardous Air Pollutant

PRODUCT OF THE UNITED STATES

Chemical percent by weight as listed in Section 3.0 is the targeted formulation quantity. Batch variation does occur and actual quantities may slightly differ.

|                      |                     |                    |
|----------------------|---------------------|--------------------|
| <b>HAZARD RATING</b> | <b>0 - MINIMAL</b>  | <b>3 - SERIOUS</b> |
|                      | <b>1 - SLIGHT</b>   | <b>4 - SEVERE</b>  |
|                      | <b>2 - MODERATE</b> | <b>* - CHRONIC</b> |

**HMIS RATING      HEALTH - \* 2      FLAMMABILITY - 2      REACTIVITY - 0**

**DATE OF PREPARATION** 01/01/18  
**EFFECTIVE DATE** 01/01/18  
**DATE PRINTED** 03/29/18