



## Rinseable Soap

### Technical Data Sheet

**Rymar Rinseable Soap** is a multi purpose cleaner for decks, fences, wood siding, and log homes. It also works well for cleaning painted or stained surfaces and vinyl siding.

**Directions:** On new & uncoated decks, siding, log homes, etc.– wet project first, (**DO NOT** use hard water when cleaning or you will end up with black iron spots). Mix 1/4 cup Rymar Rinseable Soap with 1 gallon warm water, add 1 quart chlorine bleach and mix thoroughly. Using a medium soft brush to clean project, rinse well and let dry 24 to 48 hours, then apply coating.

**To clean between coatings:** First wet surface, then mix 1/4 cup rinseable soap to 2 gallons of water. Clean with soft brush, rinse and let dry, then recoat.

**DO NOT USE BLEACH BETWEEN COATINGS.**

**To clean vinyl siding:** Use 1/4 cup soap to 2 gallons of water; scrub lightly and rinse.

**Coverage:** Approximately 2000 square feet per 16 oz. box

**Note:** Make sure you are using the proper cleaner on stains; for black spots, put a drop or two of bleach on a spot. If the spot disappears, it is mold; you will then need to use the bleach solution. If the spot does not come off, it is most likely an iron stain, use Rymar Oxalic Cleaner to remove it.

**Caution:** Always test a small area before using on an entire project. Using warm water works well, hot water will do severe damage to coatings and to some types of wood.

**DO NOT TAKE INTERNALLY!!! Avoid breathing vapor/dust. When using alone or with chlorine bleach wear gloves, respirator and proper eye protection. Read labels on bleach container.**



6620 N CTH J - CATO - WI - 54230

[www.rymarindustries.com](http://www.rymarindustries.com)

Email: [rymar@rymarindustries.com](mailto:rymar@rymarindustries.com)

Call: 920-732-3909