



EXOTIC FOREST

Technical Data

Rymar Exotic Forest Wood Sealer is a special blend of tung oil, supreme linseed oil and other proprietary resins that help penetrate the surface of exotic hardwood and softwoods. With these special oils and advanced sunscreens, Rymar Exotic Forest Wood Sealer will stand the test of time.

Product Data:

Restrictions: Apply when air and surface temperature are above 65°F and below 90°F.

Weight per gallon: 8.38

Solids by weight: 55

VOC: Less than 250 G/L

Paintable: No

Flashpoint: 105°F

Type: Natural, Semi-transparent

Vehicle: Solvent

Finish: Flat

Colors: 3 5010 Natural Translucent, 5030 Mahogany, 5040 Teak

Containers: 1 gallon

Coverage: Approximately 300-400 square feet per gallon, depending on porosity of wood.

Drying Time: Approximately 1 to 7 days depending on temperature, 30 days to full cure. All times are temperature and moisture dependent.

Clean Up: Mineral Spirits

Application: Bristle Brush, sprayer (back brushing necessary) Tip Size—.011-.013

Reduction: None

Cure: Air Dry

Substrate: Wood

Shelf Life: Approximately 2 years. Product may darken with age.

Recommended Uses:

Decks—Siding—Log Homes—Fences—Formulated for hardwoods such as Teak, IPE, and Mahogany. May also be used on softwoods.

Features & Benefits



- **Military Spec Additive**—Is a proprietary additive used by the military to enhance the longevity of coatings for specific applications.



- **Nano Particle Technology**—We incorporate nano particle technology (a shield of superfine particles) to protect wood against abrasion, UV light, and moisture.



- **Sunseal Sunscreen**— We incorporate special UV absorbers and pigments to help block out any UV light from reaching the wood surface.



- **Citronella Oil**— A naturally occurring organic substance obtained from leaves of Asiatic lemon oil grass. Commonly used as a natural mosquito repellent.



- **Chew Stop**— Is a natural pepper additive that may help prevent animals from chewing on wood. It may also discourage bees, bugs, spiders, and birds— naturally.



- **Natural and Synthetic Oils**— A blend of Supreme linseed oil and synthetic oils allows for good penetration of the wood and still gives a surface build for greater protection of the substrate.



- **PTFE**— PTFE is used to both repel water and help protect against weather erosion.



- **Water Repellent**— Other so called water repellent wood sealers can't match the water beading qualities of our sealer. Along with the oils and PTFE you get superior water protection.



EXOTIC FOREST

Technical Data

IMPORTANT INFORMATION: Rymar Exotic Forest Wood Sealer is a slow drying penetrating sealer. It is recommended that only one thin coat be applied to these types of woods. Additional coats should be applied as needed. When applying on horizontal surfaces brush out thoroughly and allow several days for product to penetrate and dry. Over application will result in prolonged dry times and possible product failure on all types of woods. Sanding with 60-80 grit sandpaper will open the pores of the wood improving the penetration, drytime and longevity. **Clear will not prevent graying as well as the pigmented color and will deteriorate at a quicker rate.**

Directions: Wood should be clean and dry. It is recommended that Rymar Rinseable Soap be used to clean the wood before sealing. If using bleach do not allow it to remain on the surface for more than five minutes. Between coats clean with Rymar Rinseable soap and water, no bleach. **DO NOT USE METAL PAILS OR HARD WATER.** Ask your dealer about preparing surfaces for coatings; they may be able to advise you otherwise depending on your situation. A coat should be applied as soon as project is completed providing the wood is at a moisture content of 15% or less and mill glaze is removed. If it is higher than 15% wait approximately three to six weeks before application. A second coat should be applied in 60-90 days. **MAINTENANCE COATS SHOULD BE DONE AS NEEDED.** Do not allow sealer to puddle. End grain on all wood should be sealed. Sealer may be applied with a bristle brush or by spraying and then back brushing. Be sure to shake well before using and stir thoroughly during use. **IF USING MULTIPLE BATCH NUMBERS, MIX THEM TOGETHER BEFORE APPLYING.**

Maintenance: For continued performance a coat of Rymar Exotic Forest Wood Coating should be applied every 18 to 24 months. In some cases Rymar Exotic Forest Wood Coating may need to be applied more often depending on weather conditions, substrate conditions, project preparation and application.

Warranty: Rymar warrants that the contents of this can are not defective. In the event this product fails to comply with the warranty, it is Rymar LLC's option to furnish replacement of the product or a refund of the purchase price with proof of purchase. In the event of product failure and/or misuse of this product, Rymar and its affiliates assume no responsibility (implied or otherwise), for labor, substrate, other items or materials used in either the application of this product or otherwise.

FYI: Proper respirator, gloves, goggles, and clothing should be used during application, be sure to check with your dealer. Check each can for color uniformity. **A brushout is recommended before doing a project.**

***NOTE! Do a test:** Try a brushout on your project to ensure the color and product is what you want before doing your entire project. **Clear will not prevent graying as well as pigmented colors.**



6620 N CTH J - CATO - WI - 54230

www.rymarindustries.com

Email: rymar@rymarindustries.com

Call: 920-732-3909